


NLB 350 Series Electric High-Pressure Water Jetting System



NLB Quick-Change
Conversion Ready



NLB's newest line of waterjetting units are built around the innovative model 350 convertible pump. This pump, with its quick-change, in-line fluid end design, has fewer parts for increased operating efficiency and simpler maintenance. And, it requires only a simple conversion kit to operate at pressures between 8,000 psi (552 bar) and 20,000 psi (1,400 bar).

The NLB 350 Series units are built using the same rugged, reliable designs have been field proven for over 30 years. The unit comes standard with features like low water pressure shutdown and a high quality electric motor starter. All operating controls, including the pressure compensating by-pass valve and pressure gauge with snubber, are mounted on a separate accessory manifold, which provides additional protection for these important components.


Features include:

- ❑ Slow running plunger pump is built from high-grade stainless steel and provides unprecedented reliability.
- ❑ Pump can be configured for pressures from 8,000 to 20,000 psi in under 30 minutes.
- ❑ NLB pressure conversion kits have fewer components.
- ❑ Accessory manifold with pressure gauge, rupture disc and by-pass valve.
- ❑ Diesel and electric-powered models are available, each mounted on a heavy-duty trailer or steel skid.



The Leader in High-Pressure Water Jet Technology

350 Series Water Blaster



Industrial Motor Drive:

Pumping system includes a TEFC electric motor and a combination non-reversing magnetic starter with fuse protection and stop/start push buttons. The system is completely pre-wired for 460 volt service and comes complete with a safety disconnect.

Model 350 - 350 hp (260 kw)

Model 300 - 300 hp (224 kw)

Model 251 - 250 hp (186 kw)

Unit Features include:

- ❑ Slow running plunger pump built from high-grade stainless steel and provides unprecedented reliability.
- ❑ Pump can be configured for pressures from 8,000 to 20,000 psi in under 30 minutes.

Skid Mounting:

- ❑ Size: 7' wide x 7' 4" high x 12' long Approx. (2.13 m wide x 2.24 m high x 3.66 m long)
- ❑ Weight 13,200 lbs. (5,987kg) Approx.

Motor Driven Pumping Assembly:

- ❑ Slow running NLB Model 350 reciprocating pump
- ❑ Three plunger lubrication
- ❑ V-belt drive with guard (optional gear pac)
- ❑ Inlet Water Filtration
- ❑ 30,000 lb. oil-filled pressure gauge with snubber
- ❑ Polypropylene water tank
- ❑ Accessory manifold with by-pass valve
- ❑ All necessary plumbing and operating controls

Specifications subject to change without notice

All Units Are Factory Tested Before Shipment

Available Pump Configurations:

Model	GPM	LPM	PSI	BAR	
Model 350 350 HP	20350E	30	113	20,000	1,400
	17350E	35	132	17,000	1,173
	15350E	40	152	15,000	1,035
	13350E	46	174	13,000	896
	10350E	60	228	10,000	700
Model 300 300 HP	8350E	74	279	8,000	552
	20300E	26	98	20,000	1,400
	17300E	31	117	17,000	1,173
	15300E	34	128	15,000	1,035
	13300E	39	147	13,000	896
Model 251 250 HP	10300E	51	194	10,000	700
	8300E	64	242	8,000	552
	20251E	21	79	20,000	1,400
	17251E	25	94	17,000	1,173
	15251E	28	106	15,000	1,035
	13251E	33	125	13,000	896
	10251E	43	163	10,000	700
	8251E	54	204	8,000	552

The 350 Series pumps can quickly be converted to operate at any of the above pressures & flows with a simple kit.



NLB can custom configure pump units to meet your specific requirements. This model has the motor positioned over the pump for a smaller footprint.



The Leader in High-Pressure Water Jet Technology

Headquarters

29830 Beck Road
Wixom, MI 48393-2824
(248) 624-5555
FAX: (248) 624-0908
<http://www.nlbcorp.com>

Regional Offices

159 Harmony Road, Mickleton, NJ 08056
(856) 423-2211 FAX: (856) 423-0997
201 S. 16th, La Porte, TX 77571
(281) 471-7761 FAX: (281) 471-8738

14302 Highway 44 N., Gonzales, LA 70737
(225) 622-1666 FAX: (225) 622-7366
1323 E. Hill St., Signal Hill, CA 90755
(562) 490-3277 FAX: (562) 733-0780